



P-Channel Enhancement-Mode Vertical DMOS FETs

Ordering Information

BV _{DSS} / BV _{DGS}	R _{DS(ON)} (max)	I _{D(ON)} (min)	Order Number / Package		
			TO-3	TO-220	Die†
-500V	7.5Ω	-1A	VP0350N1	VP0350N5	VP0350ND

† MIL visual screening available

High Reliability Devices

See pages 5-4 and 5-5 for MILITARY STANDARD Process Flows and Ordering Information.

Features

- Free from secondary breakdown
- Low power drive requirement
- Ease of paralleling
- Low C_{iss} and fast switching speeds
- Excellent thermal stability
- Integral Source-Drain diode
- High input impedance and high gain
- Complementary N- and P-channel devices

Applications

- Motor controls
- Converters
- Amplifiers
- Switches
- Power supply circuits
- Drivers (relays, hammers, solenoids, lamps, memories, displays, bipolar transistors, etc.)

Absolute Maximum Ratings

Drain-to-Source Voltage	BV _{DSS}
Drain-to-Gate Voltage	BV _{DGS}
Gate-to-Source Voltage	± 20V
Operating and Storage Temperature	-55°C to +150°C
Soldering Temperature*	300°C


* Distance of 1.6 mm from case for 10 seconds.

Advanced DMOS Technology

These enhancement-mode (normally-off) transistors utilize a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces devices with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, these devices are free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Package Options



Thermal Characteristics

Package	I _D (continuous)*	I _D (pulsed)	Power Dissipation @ T _C = 25°C	θ _{JC} °C/W	θ _{JA} °C/W	I _{DR} *	I _{DRM}
TO-3	-1.5A	-3.0A	100W	1.25	30	-1.5A	-3.0A
TO-220	-1.0A	-3.0A	50W	2.5	40	-1.0A	-3.0A

* I_D (continuous) is limited by max rated T_J.


Electrical Characteristics (@ 25°C unless otherwise specified)

Symbol	Parameter	Min	Typ	Max	Unit	Conditions
BV _{DSS}	Drain-to-Source Breakdown Voltage	-500			V	V _{GS} = 0V, I _D = -10mA
V _{GS(th)}	Gate Threshold Voltage	-2.5		-4.5	V	V _{GS} = V _{DS} , I _D = -10mA
ΔV _{GS(th)}	Change in V _{GS(th)} with Temperature		4.8	6.0	mV/°C	V _{GS} = V _{DS} , I _D = -10mA
I _{GSS}	Gate Body Leakage			-100	nA	V _{GS} = ±20V, V _{DS} = 0V
I _{DSS}	Zero Gate Voltage Drain Current			-200	μA	V _{GS} = 0V, V _{DS} = Max Rating
				-2	mA	V _{GS} = 0V, V _{DS} = 0.8 Max Rating T _A = 125°C
I _{D(ON)}	ON-State Drain Current		-1.5		A	V _{GS} = -5V, V _{DS} = -25V
		-1.0	-3.0			V _{GS} = -10V, V _{DS} = -25V
R _{DS(ON)}	Static Drain-to-Source ON-State Resistance		6.0		Ω	V _{GS} = -5V, I _D = -0.25A
			5.5	7.5		V _{GS} = -10V, I _D = -0.25A
ΔR _{DS(ON)}	Change in R _{DS(ON)} with Temperature		0.7	1.2	%/°C	V _{GS} = -10V, I _D = -0.25A
G _{FS}	Forward Transconductance	0.25	0.45		∅	V _{DS} = -25V, I _D = -0.5A
C _{ISS}	Input Capacitance		720	800	pF	V _{GS} = 0V, V _{DS} = -25V f = 1 MHz
C _{OSS}	Common Source Output Capacitance		110	130		
C _{RSS}	Reverse Transfer Capacitance		20	50		
t _{d(ON)}	Turn-ON Delay Time		11	30	ns	V _{DD} = -25V I _D = -1A R _{GEN} = 10Ω
t _r	Rise Time		11	30		
t _{d(OFF)}	Turn-OFF Delay Time		70	100		
t _f	Fall Time		22	30		
V _{SD}	Diode Forward Voltage Drop		-1.0	-1.3	V	V _{GS} = 0V, I _{SD} = -0.25A
t _{rr}	Reverse Recovery Time		550		ns	V _{GS} = 0V, I _{SD} = -0.25A

Notes:


- All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300μs pulse, 2% duty cycle.)
- All A.C. parameters sample tested.

Switching Waveforms and Test Circuit




Typical Performance Curves


Output Characteristics




Saturation Characteristics




Transconductance vs. Drain Current




Power Dissipation vs. Case Temperature



Maximum Rated Safe Operating Area




Thermal Response Characteristics




Typical Performance Curves


BV_{DSS} Variation with Temperature




On-Resistance vs. Drain Current




Transfer Characteristics



V_(th) and R_{DS} Variation with Temperature



Capacitance vs. Drain-to-Source Voltage



Gate Drive Dynamic Characteristics

