

2. Product Specifications

GENERAL	Power Requirements	AC 220-240V, 50/60Hz (AC110-240V : CIS Model)
	Power Consumption	25Watts
	Weight	4.3kg
	Dimensions	W 430mm x D 330mm x H 100mm
	Operating ambient Temperature	+5°C ~ +35°C
	Installation conditions	Operation position : Horizontal, Relative humidity : Below 75%
INPUT	Video input (Rear)	RCA jack : 1.0Vp-p (unbalanced) 75Ω
	Audio input (Rear)	RCA jack : -8dBm, 47Kohm unbalanced
OUTPUT	RF out	UHF 21-69 (Initial CH36)
	Audio (DVD, VCR)	RCA jack, Euro Scart socket
	Audio (DVD only)	Digital audio out (OPTICAL, COAXIAL)
	Video (DVD, VCR)	RCA jack, Euro Scart socket
	Video (DVD only)	S-Video out
		RGB out : Euro Scart socket
VCR	Tape format	VHS type video tape,
		S-VHS type video tape (Playback only)
	Color system	PAL, MESECAM, NTSC4.43, NTSC playback on PAL TV, SECAM(OPTION)
	Tuning system	B/G, D/K, I(U.K), L(FRANCE)
	Video S/N	Above 43dB (standard recording)
	Resolution	Above 240 lines (standard recording)
	Audio S/N	Above 68dB (Hi-Fi), 39dB (Mono)
DVD	Audio frequency characteristics	20Hz - 20KHz (Hi-Fi)
	Disc	DVD, CD (12cm), CD (8cm), VIDEO-CD (12cm), MP3, CD-R(RW)
	Audio S/N	115dB
	Audio dynamic range	105dB

MEMO